

SCHULTE®

Series 3

XH1500/XH1000 ROTARY CUTTERS



- Heavy Duty Stump Jumper & Deck Rings -



- Ultra Narrow Transport Width -



Tandem Walking Axles Deck Protection Rings New Single Domed Deck

- 1** Single domed, sweep clean deck design eliminates excess weight over competitive double deck designs, eliminates build up of debris and prevents rusting on top side of deck
- 2** Tandem walking axles result in smooth operation over rough surfaces
- 3** Increased frame depth & blade tip speed results in a superior flow of material
- 4** With larger 24" aircraft tires, transport height is increased to 17.5" along with improved performance in wet conditions
- 5** Lower pressure 8" stroke hydraulic phasing cylinders for a level lift
- 6** Low maintenance Constant Velocity Tractor Shaft or Patent Pending 540rpm Equal Angle Hitch available
- 7** Center suspension reduces stress on tractor drawbar
- 8** 3/8" thick formed deck protection rings prevent blade to deck contact
- 9** Double safety chains with individually replaceable links are standard equipment
- 10** Large high horsepower gearboxes with 1-3/4" input shafts and 2-3/8" output shafts, 260hp divider, 190hp center & wings
- 11** Higher slip clutch release settings than previous design ensures better performance in rough cutting
- 12** 1/4" thick stump jumpers with patent pending Pentagon Blade Bolt design allows cutter sections to ride over obstructions

G O N U M B E R O N E . . . G O S C H U L T E !

Unparalleled Cutting Performance

SPECIFICATIONS XH1500

Cutting width	180" (4.57m)	126" (3.20m)
Overall width	190" (4.83m)	139" (3.53m)
Overall length	192" (4.88m)	192" (4.88m)
Transport width, min	88" (2.24m)	88" (2.24m)
Transport height	88" (2.24m)	88" (2.24m)
Deck thickness	7GA (3/16") (4.6mm)	7GA (3/16") (4.6mm)
Weight, approx.	5800 lbs (2636kg)	5200 lbs (2364kg)
Hitch weight, approx.	1900 lbs (864kg)	1700 lbs (773kg)
Minimum tractor HP	65 HP (52kW)	50 HP (45kW)
Recommended tractor HP	85 HP (67kW)	75 HP (60kW)
Cutting height	1.5" to 17.5" (38 to 456mm)	
Ground clearance	17.5" (444mm)(with 24" tire)	
Cutting capacity	4" material (102mm)	
Blade overlap	6.5" (165mm)	
Divider gearbox rating	260 HP (194kW)	
Centre/wing gearbox rating	190 HP (142kW)	
Blade tip speed,	540 rpm	
Centre	848 rpm, 15,493 ft/min (4874m/min)	
Wing	986 rpm, 15,991 ft/min (4722m/min)	
Blade tip speed,	1000 rpm	
Centre	850 rpm, 15,743 ft/min (4884m/min)	
Wing	1002 rpm, 16,022 ft/min (4798m/min)	
Wing working range	25° down to 90° up	

OPTIONS

540rpm Equal Angle hitch, precision hitch, precision clevis hitch, standard clevis hitch, 540 or 1000 rpm drive packages, aircraft tires, foam filled aircraft tires, solid laminated tires, towing hitch kit, manual winch kit, spool valve kit, shredder blade kit, wing walking axles, safety lighting kit, optional rubber guard kit for front edge and tool box kit.



- Our stump jumpers are built to last -



- Patent pending Pentagon Blade Bolt design with replaceable bushings -
- Flat 1" thick blade bar design with heavy duty bracing -

Schulte's all new XH1500 and XH1000 Rotary Cutters offer unparalleled cutting performance for demanding commercial and agricultural use. Increased blade tip speeds and greater space under the deck contribute to clean cutting in all conditions. A center suspension system reduces stress to the rotary cutter and the tractor. Industry leading transport clearance improves performance in rough terrain. New low maintenance constant velocity tractor drive shafts require weekly, rather than daily service.

STANDARD FEATURES

Blade pans have 1/4" thick skins and flat blade bar, blade bolts with pentagon lock and pentagon sleeve, high capacity 5 bolt wheel hubs, replaceable axles, integrated center and wing transport locks, wings float 35° up to 25° down without pumping hydraulic cylinders, large diameter two plate clutches with nitrided surfaces, free floating hitch, leveling adjustments on each wing, retractable wing wheels for narrow transport, double chains front & rear.



① Equal Angle Hitch (540rpm only)



② Precision Hitch

③ Precision Clevis Hitch

④ Standard Clevis Hitch



The new Schulte FLX15/FLX10 Flex-Arm is the perfect attachment for the XH1500/XH1000 Series 3 rotary cutters

SCHULTE

MEMBER OF THE
ALAMO GROUP
ALWAYS ON THE CUTTING EDGE.

Schulte Industries Ltd.,

P.O. Box 70, Englefeld, Saskatchewan, Canada S0K 1N0

Tel: (306) 287-3715 Fax: (306) 287-3355

E-Mail: info@schulte.ca

Visit our Web site at: www.schulte.ca

ISO 9001:2000



Schulte Industries Ltd. reserves the right to change the design, material and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment. Part No. 1000-147

Sold By: